CHANDRA DYNAMO TRACK LIGHTING Track Fixture

eralux







DATE
PROJECT NAME

TYPE

QTY

ORDERING CODE AE-TL-CD12 NF N30 J1 WH DYN

The CHANDRA series track lighting fixture is specifically designed for the retail environment. It distinguishes itself with its sleek look, variety of optical options, and a series of accessories to adapt to every possible scenario. The installation of accessories on this product is simply a breeze. This enables fast deployment of fixtures around stores for reconfigurations of products. This product comes at standard 90 CRI, but also caters for lighting experts with a high-GAI (Gamut Area Index) option for an enhanced visual effect on products.

OPERATING & ELECTRICAL INPUT VOLTAGE 120 V POWER FACTOR 0.9 DIMMING Triac dimming TOTAL HARMONIC DISTORTION (THD)

PERFO	RMANCE
LUMENS PER WATT	~111 LPW at 80CRI 2000 lumens at 3000K
POWER CONSUMPTION	18W
DISTRIBUTION	Narrow flood (15 deg)

MECHANICAL & HOUSING				
HOUSING	Aluminum die cast			
LENS	Highly durable polycarbonate and high transmittance lens			
FINISH	White			
POWER SUPPLY	Factory wired electronic LED driver			
LED BOARD	СОВ			

APPLICATION CONDITION

AMBIENT TEMPERATURE -10 °C to 35°C RANGE

COMPATIBLE MOUNTING

MOUNTING

Juno
Global
Halo
Lightolier

WARRANTY

SYSTEM WARRANTY - 5 YEARS

Eralux will warrant defective drivers, LEDs and boards for 10 years from the date of purchase. This warranty is valid only if the fixture is installed and used as per installation guides and specifications. If a defect is present, Eralux will send drivers and boards at no fee with a thorough replacement instructions along with instructions on the return of the defective parts back to Eralux.

LUMEN MAINTENANCE - L70 at 50,000 hours

Rated for 85% initial lumen output at 50,000 hours of operation, operated at 25°C ambient temperature; per guidelines published by the Illuminating Engineering Society (IES)



Track Fixture


DATE						
PROJECT NAME						
TYPE						
QTY						
ORDERING CODE	AE-TL-CD12	NF	N30	J1	WH	- DYN

ORDERING CHIDE

OKDEKING G	סוטב		EXAMPLE: AE-TL-CD12NFN30J1WH-DY			
FIXTURE FAMILY	VOLTAGE	DISTRIBUTION	CRI	сст	ADAPTER	FINISH
AE-TL-CD	12					
AE-TL-CD Chandra Dynamo Series track light	12 120V	NF Narrow Flood light distribution 18 watts: 2000 lumens at 80CRI 3000K	N Normal 80 CRI	30 3000K CCT	J1 Juno mounting system	WH-DYN White powder coat finish
						BK-DYN Black powder coat finish

PRODUCT DIMENSIONS

AE-TL-CD12XXXXXXXXX



eralux CHANDRA

PROJECT NAME

TYPE

QTY

ORDERING
CODE

AE-TL-CD12

NF N30 J1 WH DYN

TRACK LIGHTING
Track Fixture


LUMEN ESTIMATE


Lumen output varies based on CCT and CRI. An estimate of lumen output of the various CCT/CRI combinations, use correction factors as per table below:

LUMEN ESTIMATE ADJUSTMENT FACTORS					
ССТ	3000K	3500K	4000K		
PREMIUM (90CRI)	1	1.03	1.06		
SUPERIOR (HIGH GAI)	.90	.96	N/A		

PHOTOMETRIC DATA

AE-TL-CD12WFP30XXXX-DYN





DIMMER COMPATIBILITY LIST

120 V Dimmers

MANUFACTURER	PART NUMBER
	DV-600P
	DVELV-303P
	NTELV-600
LUTRON	MAELV-600
20111.011	DVLV-600P
	SELV-300P
	NFTU-5A
	CTCT-153P
	GL-600H
	S-600P
	РНРМ

ACCESSORIES

Ordered separately, field installed



Hexcell Louver AE-TL-CD-HX



Snoot
AE-TL-CD-SNT-BK
AE-TL-CD-SNT-WH

eralux CHANDRA

TRACK LIGHTING

Track Fixture

DATE						
PROJECT NAME						
TYPE						
QTY						
ORDERING CODE	AE-TL-CD12	NF	N30	J1	WH	- DYN

