

ATLANTIS

GYPSUM LINEAR FIXTURES

Linear Architectural Lighting

The Atlantis Series is a recessed linear that provides an elegant appearance in any indoor commercial office. The exposed driver and the removable lens makes the installation simple and intuitive. This series has been designed to be mounted into gypsum ceilings or walls.



eralux®



DATE					
PROJECT NAME					
TYPE					
QTY					
ORDERING CODE	AE-SF-ATL				

OPERATING & ELECTRICAL

INPUT VOLTAGE	120-277 V
POWER FACTOR	0.9
DIMMING	0-10V
TOTAL HARMONIC DISTORTION (THD)	<20%

PERFORMANCE

LUMENS PER WATT	85-89 LPW at 80CRI
POWER	32W 40W 46W 62W
DISTRIBUTION	Lambertian

MECHANICAL & HOUSING

HOUSING	Extruded aluminum
LENS	Highly durable frosted polycarbonate and high transmittance lens
FINISH	White, Black, Silver
POWER SUPPLY	Factory wired electronic LED driver
LED BOARD	Discrete LED

APPLICATION CONDITION

AMBIENT TEMPERATURE RANGE	-10°C to 40°C
---------------------------	---------------

COMPATIBLE MOUNTING

MOUNTING	Recessed (Non-IC rated)
----------	-------------------------

WARRANTY

SYSTEM WARRANTY – 5 YEARS

Eralux will warrant defective drivers, LEDs and boards for 5 years from the date of purchase. This warranty is valid only if the fixture is installed and used as per installation guides and specifications. If a defect is present, Eralux will send drivers and boards at no fee with a thorough replacement instructions along with instructions on the return of the defective parts back to Eralux.

LUMEN MAINTENANCE – L85 at 50,000 hours

Rated for 85% initial lumen output at 50,000 hours of operation, operated at 25°C ambient temperature; per guidelines published by the Illuminating Engineering Society (IES).

DATE	
PROJECT NAME	
TYPE	
QTY	
ORDERING CODE	AE-SF-ATL

ORDERING GUIDE

EXAMPLE: AE-SF-ATL35432WH



FIXTURE FAMILY	CCT	LENGTH	POWER	FINISH
AE-SF-ATL				
AE-SF-ATL ERALUX Atlantis linear architectural fixture – 120-277V	30 3000K	4 4 feet length	32 32 watts: 2720 lumens	WH White Finish
	35 3500K	5 5 feet length	40 40 watts: 3400 lumens	BK Black Finish
	40 4000K	6 6 feet length	46 46 watts: 4080 lumens	SV Silver Finish
		8 8 feet length	62 62 watts: 5440 lumens	

FIXTURE FAMILY	CCT	SHAPE	POWER	FINISH
AE-SF-ATL				
AE-SF-ATL ERALUX Atlantis linear architectural fixture – 120-277V	30 3000K	90L L Shape	32 32 watts: 2720 lumens	WH White Finish
	35 3500K	90N Inner L Shape	32 32 watts: 2720 lumens	BK Black Finish
		90W Outer L Shape	32 32 watts: 2720 lumens	
	40 4000K	T T Shape	46 46 watts: 4080 lumens	SV Silver Finish
		X X Shape	62 62 watts: 5440 lumens	

CAUTION: If there are multiple fixtures connected to the same 0-10V dimming line, a 0-10V controller must be considered to enable consistent dimming across the fixtures. Failure to do so will lead to inconsistent dimming and behaviors in the fixtures. Single switch is not recommended for controlling multiple fixtures simultaneously.

PRODUCT DIMENSIONS (in mm)

AE-SF-ATLXXXXWH




DATE	
PROJECT NAME	
TYPE	
QTY	
ORDERING CODE	AE-SF-ATL

VARIOUS SHAPES

L SHAPE



AE-SF-ATLXX90L32XX



DIMENSIONS IN INCHES



OUTER CORNER L

AE-SF-ATLXX90W32XX





INNER CORNER L

AE-SF-ATLXX90N32XX



T SHAPE



AE-SF-ATLXXT46XX



DIMENSIONS IN INCHES

X SHAPE

AE-SF-ATLXXX62XX



DIMENSIONS IN INCHES

DATE	
PROJECT NAME	
TYPE	
QTY	
ORDERING CODE	AE-SF-ATL


LUMEN ESTIMATE

Lumen output varies based on CCT and CRI. An estimate of lumen output of the various CCT/CRI combinations, use correction factors as per table below:


LUMEN ESTIMATE ADJUSTMENT FACTORS				
CCT	2700K	3000K	3500K	4000K
PREMIUM (80CRI)	0.91	0.94	0.97	1

PHOTOMETRIC DATA

AE-SF-ATL40432WH
4 FEET
32 WATTS

ZONAL LUMEN SUMMARY			POLAR LUMINOUS INTENSITY GRAPH
ZONE	LUMENS	% OF FIXTURE	
0-20°	402.84	14.7	
0-30°	834.83	30.5	
0-40°	1326.9	48.5	
0-60°	2212.54	80.90	
0-80°	2663.34	97.40	
0-90°	27015	98.80	

AE-SF-ATL40432WH
4 FEET
62 WATTS

ZONAL LUMEN SUMMARY			POLAR LUMINOUS INTENSITY GRAPH
ZONE	LUMENS	% OF FIXTURE	
0-20°	805.36	14.70	
0-30°	1668.98	30.50	
0-40°	2652.73	48.50	
0-60°	4423.29	80.90	
0-80°	5324.52	97.40	
0-90°	5400.81	98.80	

DATE	
PROJECT NAME	
TYPE	
QTY	
ORDERING CODE	AE-SF-ATL

OVERVIEW

EASE OF ACCESS TO DRIVER

Outer Driver making the installation and assembly process quick and easy.

N-SHAPE RECESSED CLIP

Strong N-shape recessed clip replacing spring clip allowing recessed to not only ceiling but vertical wall without sliding nor falling. The unique design of the clip shape simplify the installation process.

ELEGANT WHITE FINISH




Uniformed nebula white finish provides a simple and elegant appearance making any indoor project superior.

UGR<19

Unified Glare Rating of 19 or less makes Atlantis a perfect lighting option in office spaces where workers need to spend many hours a day and would be using display terminals for a large proportion of that time.

SPACE-SAVING FLAT SHAPE

Flat fixture body saves space for installation, make the linear fixture more flexible for various purpose.



ATLANTIS

GYPSUM LINEAR FIXTURES

Linear Architectural Lighting

DATE					
PROJECT NAME					
TYPE					
QTY					
ORDERING CODE	AE-SF-ATL				

Draw your custom shape!

1 square = 1ft

