CHANDRA MINI

TRACK LIGHTING

Track Fixture

With the CHANDRA Max and CHANDRA Series, you can create a family look in your retail environment with the new CHANDRA Mini series. It comes available in a variety of beam patterns and CCT options. With a 90CRI for all its CCT, the CHANDRA Mini will enhance your retail environment to another level.



OPERATING & ELECTRICAL				
INPUT VOLTAGE	120 V			
POWER FACTOR	>0.9			
DIMMING	Triac dimming			
TOTAL HARMONIC DISTORTION (THD)	<20%			

PERFORMANCE					
LUMENS PER WATT	79-91 LPW at 90CRI				
POWER CONSUMPTION	9W,13.4W				
DISTRIBUTION	Narrow flood Flood Wide flood				

MECHANICAL & HOUSING						
HOUSING	Aluminum die cast					
LENS	Highly durable polycarbonate and high transmittance lens					
FINISH	Black, White, Silver					
POWER SUPPLY	Factory wired electronic LED driver					
LED BOARD	СОВ					

APPLICATION CONDITION

AMBIENT TEMPERATURE	-10 °C to 35°C
RANGE	-10 C 10 33 C

COMPATIBLE MOUNTING

	Juno
MOUNTING	Global
MOUNTING	Halo
	Lightolier

WARRANTY

SYSTEM WARRANTY - 5 YEARS

Eralux will warrant defective drivers, LEDs and boards for 5 years from the date of purchase. This warranty is valid only if the fixture is installed and used as per installation guides and specifications. If a defect is present, Eralux will send drivers and boards at no fee with a thorough replacement instructions along with instructions on the return of the defective parts back to Eralux.

LUMEN MAINTENANCE - L70 at 50,000 hours

Rated for 70% initial lumen output at 50,000 hours of operation, operated at 25°C ambient temperature; per guidelines published by the Illuminating Engineering Society (IES)

eralux[®] **CHANDRA MINI**

TRACK LIGHTING
Track Fixture


DATE					
PROJECT NAME					
TYPE					
QTY					
ORDERING CODE	AE-TL-CDM-12		Р		

ORDERING GUIDE

EV A MADIE.	A E TI CDAA	-12LNFP30J1BK
EXAMPLE:	AE-IL-CDM-	· I Z L N F P 3 U J

FIXTURE FAMILY	WATTAGE	DISTRIBUTION	CRI	ССТ	ADAPTER	FINISH
AE-TL-CDM-12			P			
AE-TL-CDM-12 ERALUX CHANDRA MINI track light 120V	9 watts: 880 lumens at 90CRI 3000K	SP Spotlight distribution 21° 4239 @ 9W 6226 @ 13.4 W	Premium 90 CRI	27 2700K CCT	J1 Juno mounting system	BK Black powder coat finish
		NF Narrow Flood light distribution 24° CBCP: 3175 @ 9W 4499 @ 13.4 W		30 3000K CCT	G1 Global mounting system	
		FL Flood light				WH White powder
	H 13.4 watts:	distribution 29°		35	H1 Halo mounting system	coat finish
	1,220 lumens at 90CRI 3000K	2437 @ 9W 3424 @ 13.4W		3500K CCT		SV Silver powder coat finish
		WF Wide Flood light distribution 55° CBCP: 943 @ 9W 1328 @ 13.4W		40 4000K CCT	L1 Lightolier mounting system	

PRODUCT DIMENSIONS





DATE					
PROJECT NAME					
TYPE					
QTY					
ORDERING CODE	AE-TL-CDM-12		P		

TRACK LIGHTING
Track Fixture

LUMEN ESTIMATE

Lumen output varies based on CCT and CRI. An estimate of lumen output of the various CCT/CRI combinations, use correction factors as per table below:

LUMEN ESTIMATE ADJUSTMENT FACTORS					
ССТ	2700	3000K	3500K	4000K	
PREMIUM (90CRI)	0.8	0.86	0.93	0.93	

PHOTOMETRIC DATA

AE-TL-CDM-12HSPP30X1XX Spot 21°

ZONA	ZONAL LUMEN SUMMARY		ZONAL LUMEN SUMMARY		POLAR LUMINOUS INTENSITY GRAPH
ZONE	LUMENS	% OF FIXTURE	4650		
0-20°	844.87	74.3	3702		
0-30°	989.98	87.1	155%		
0-40°	1050.69	92.4			
0-60°	1083.89	95.3			
0-80°	1096.9	96.5			
0-90°	1102.58	97			

AE-TL-CDM-12HNFP30X1XX Narrow Flood 25°

ZONA	AL LUMEN SUM	MARY	POLAR LUMINOUS INTENSITY GRAPH
ZONE	LUMENS	% OF FIXTURE	3368
0-20°	769.87	71.4	2246
0-30°	923.22	85.7	
0-40°	982.35	91.1	
0-60°	1020.44	94.7	
0-80°	1034.35	96	
0-90°	1040.5	96.5	



DATE					
PROJECT NAME					
TYPE					
QTY					
ORDERING CODE	AE-TL-CDM-12		Р		

PHOTOMETRIC DATA (CONTINUE)

AE-TL-CDM-12HFLP30X1XX Flood 29°

Track Fixture

ZONA	AL LUMEN SUM	MARY	POLAR LUMINOUS INTENSITY GRAPH
ZONE	LUMENS	% OF FIXTURE	255/
0-20°	716.82	66.8	
0-30°	913.59	85.2	856
0-40°	974.93	90.9	
0-60°	1012.94	94.4	
0-80°	1027.24	95.8	
0-90°	1033.71	96.4	

AE-TL-CDM-12HWFP30X1XX Wide Flood 55°

ZONAL LUMEN SUMMARY		MARY	POLAR LUMINOUS INTENSITY GRAPH			
ZONE	LUMENS	% OF FIXTURE	1995			
0-20°	468.01	41.2				
0-30°	836.41	73.6				
0-40°	1012.72	89.1				
0-60°	1076.6	94.8				
0-80°	1090.49	96				
0-90°	1097.06	96.6				

eralux® CHANDRA MINI

TRACK LIGHTING
Track Fixture

DATE		
PROJECT NAME		
TYPE		
QTY		
ORDERING CODE	AE-TL-CDM-12	

DIMMER COMPATIBILITY LIST (10 & 13.5W)

TRIAC/ELV Dimmer @120VAC
Lutron SLV-600X
Lutron S2-LX
Lutron GL-600H
Lutron NFTU-5A
Lutron DVLV-600P
Leviton 6602-X
Leviton 6681-X
Leviton 6683-X

TRIAC/ELV Dimmer @120VAC
Leviton 6684-X
Leviton 700-X
Leviton 705-X
Leviton 6633
Leviton 6674
Leviton IPI06-1LZ
Cooper 9530XXX
Lightolier MP600X
Advance \$R150LED120

ACCESSORIES

Ordered separately, field installed

FIXTURE FAMILY	ACCESSORY	PICTURE
AE-TL-CDM-		
AE-TL-CDM-	HX Hexcell Louver	
	SNT-BK Snoot Black	
	SNT-WH Snoot White	

eralux® CHANDRA MINI

TRACK LIGHTING
Track Fixture

DATE					
PROJECT NAME					
TYPE					
QTY					
ORDERING CODE	AE-TL-CDM-12		Р		

OVERVIEW





MULTIPLE MOUNTING ADAPTERS

Choose from any of the popular track systems such as Juno, Halo, Lightolier, or Global.

PREMIUM DESIGN

Aluminum die-cast materials selected for efficient thermal heat dissipation, enhanced structural rigidity maximizing LED life and driver function.

MULTIPLE OPTIONS

Customize your track head by selecting from a variety of beam angle and CCT options allowing you to have a unique fixture that suits your project.

PAINT FINISH

Factory standard in black, white, and silver. Contact for custom paint finishes to enhance your fixture to suit your project space.

EFFICIENT DESIGN

Integrated components allow for small stem and clean aesthetic appearance.





