EVEREST				eralux®				
					DATE	QTY	ACC. QTY	ΤΥΡΕ
mmercial LED Lighting								
-Lens Troffer J 🗇 🗸 2x4			P	ROJECT				
rest is a tri-lengenerative cal Troff what offers superior lighting for your applica- ilable in two sizes: 2x2' and the switchable CCT and power options. It provi ibility in terms of brightness and color the parature for any installation, with effic			/ up	PN ESSORY PN				
10 LPW. lications: Commercial Office	Health re   Sc	hools   Retail Merchandising Ar		NOTES				
رالک <sub>ا</sub> DYNA	C MENU			-				
Ordering Guide	Page							
Dimensions	<u>ve 3</u>							
Control	Page						1	
Photometric Data	Page 8							
Input Voltage	120-347V		VER I	CCT		<u>((</u> *	))	
Power Factor	>0.9		HER HICHABLE			<u>((</u> <del>*</del>	)	
					Emergency backup battery	Motion S	enor	
Total Harmonic Distortion	<20%							
Dimming page 9	0-10V Dimming			PRODUCT CERTIFICATIONS				
CRI	80 CRI	e	YEARS VARRANTY Praly	Rou				
сст	35К 40К		SYSTEM WARRANTY – 5 YEARS					
Lumens Per Watt	2X2' 24/30/36W in:		ralux will rom the dat	a der te of yrcha			nd boards f lid only if th	
Power			installed and used to installation guides and specifications. If a defect is present, Era will send drift, and boards at no fee with a					
			horough rep eturn of the				instructions	on the
Ambient Temperature Range	-25°C to 40°C						: <u>50</u> ,000 hou	ırs
Distribution	120° —		Rated for 70% initial lumen exput at 50,00 hours of operation, operated at 25°C ambient to operature; per suidelines published by					
Mounting options <sub>page 5</sub>			•	uminating Engineering Society (IES)				