


# F2 UGR

## LINEAR SURFACE MOUNT

Linear Architectural Lighting

The F2 series is the surface mount linear architectural lighting fixture from ERALUX. The F2 Series offers the simplicity of installation for a fast and efficient delivery. It is further enhanced with the access to the led board, drivers and any other components from below. They are available in 4-, 6- and 8-feet lengths. The CCT switchable switch also enables a rapid change of lighting environment.



eralux®



DATE

PROJECT NAME

TYPE

QTY

ORDERING  
CODE

AE-SF-F2-

-

-30/40/CCT-

UGR-

### OPERATING & ELECTRICAL

INPUT VOLTAGE 120-277V

POWER FACTOR 0.9

DIMMING 1-10V

TOTAL HARMONIC  
DISTORTION (THD) <20%

### PERFORMANCE

LUMENS PER FEET 585 lm/ft

POWER 23W  
31W  
46W  
61W

BEAM ANGLE Lambertian

### MECHANICAL & HOUSING

HOUSING Extruded aluminum

LENS PC Lens

FINISH Nebula White  
Atomic Black  
Silver

POWER SUPPLY Factory wired electronic LED driver

LED BOARD LED Array

### APPLICATION CONDITION

AMBIENT TEMPERATURE  
RANGE -20°C to 45°C

### COMPATIBLE MOUNTING

MOUNTING Surface Mount

### WARRANTY

SYSTEM WARRANTY – 5 YEARS

Eralux will warrant defective drivers, LEDs and boards for 5 years from the date of purchase. This warranty is valid only if the fixture is installed and used as per installation guides and specifications. If a defect is present, Eralux will send drivers and boards at no fee with a thorough replacement instructions along with instructions on the return of the defective parts back to Eralux.

LUMEN MAINTENANCE – L85 at 50,000 hours

Rated for 85% initial lumen output at 50,000 hours of operation, operated at 25°C ambient temperature; per guidelines published by the Illuminating Engineering Society (IES).

# F2 UGR

LINEAR SURFACE MOUNT

Linear Architectural Lighting

DATE	
PROJECT NAME	
TYPE	
QTY	
ORDERING CODE	AE-SF-F2- - -30/40/CCT- UGR-

## ORDERING GUIDE

EXAMPLE: AE-SF-F2-4-31-30/40/CCT-UGR-BK



FIXTURE FAMILY	LENGTH	POWER	CCT	LENS	FINISH
<b>AE-SF-F2-</b>		<b>-</b>	<b>-30/40/CCT-</b>	<b>UGR-</b>	
<b>AE-SF-F2-</b> ERALUX F2 surface mount linear architectural fixture	<b>3</b> 3 Feet	<b>-23</b> 23W-1,755 lumens	<b>-30/40/CCT-</b> CCT Switchable: 3000K/3500K/4000K	<b>UGR-</b> Low UGR Lens	<b>BK</b> Atomic Black Finish
	<b>4</b> 4 Feet	<b>-31</b> 31W-2,340 lumens			<b>WH</b> Nebula White Finish
	<b>6</b> 6 Feet	<b>-46</b> 46W-3,510 lumens			<b>SV</b> Silver Finish
	<b>8</b> 8 Feet	<b>-61</b> 61W-4,680 lumens			<b>RALXXXX</b> Custom Colour

FIXTURE FAMILY	SHAPE	CCT	LENS	FINISH
<b>AE-SF-F2-</b>		<b>-30/40/CCT-</b>	<b>-UGR</b>	
<b>AE-SF-F2-</b> ERALUX F2 surface mount linear architectural fixture	<b>L-90L</b> L Shape 31W-2,340 lumens	<b>-30/40/CCT-</b> CCT Switchable: 3000K/3500K/4000K	<b>-UGR</b> Low UGR Lens	<b>BK</b> Atomic Black Finish
	<b>T-</b> T Shape 46W-3,510 lumens			<b>WH</b> Nebula White Finish
	<b>X-</b> X Shape 61W-4,680 lumens			<b>RALXXXX</b> Custom Colour

CAUTION: If there are multiple fixtures connected to the same 1-10V dimming line, a 1-10V controller must be considered to enable consistent dimming across the fixtures. Failure to do so will lead to inconsistent dimming and behaviors in the fixtures. Single switch is not recommended for controlling multiple fixtures simultaneously.

## PRODUCT DIMENSION

AE-SF-F2-4/6/8 FT





DIMENSIONS IN INCHES

DATE	
PROJECT NAME	
<b>TYPE</b>	
QTY	
ORDERING CODE	AE-SF-F2- - -30/40/CCT- UGR-

## VARIOUS SHAPES

### L SHAPE



AE-SF-F2-L-90L-30/35/40/CCT-UGR-XX



DIMENSIONS IN INCHES

### T SHAPE



AE-SF-F2-T-30/35/40/CCT-UGR-XX



DIMENSIONS IN INCHES



### X SHAPE

AE-SF-F2-X-30/35/40/CCT-UGR-XX





DIMENSIONS IN INCHES

## MULTIPLE FIXTURE ASSEMBLY



## ACCESSORIES

Ordered separately, field installed

PART NUMBER	DESCRIPTION	PICTURE
AE-SF-F2-LINK-KIT	Linkable mechanical and electrical accessories for continuous mounting	
AE-SF-L-DA	Rubber Diffuser Sucker and F2 Disassembly spanner	

**RAL9006**  
**Silver**

**RAL9004**  
**Black**

**RAL9003**  
**White**



DATE	
PROJECT NAME	
TYPE	
QTY	
ORDERING CODE	AE-SF-F2- - -30/40/CCT- UGR-

## CUSTOMED FINISH EXAMPLES FOR F2 AIR

\* Please contact manufacturer for more information and pricing for customized finishes



DATE					
PROJECT NAME					
TYPE					
QTY					
ORDERING CODE	AE-SF-F2-	-	-30/40/CCT-	UGR-	

## LUMEN ESTIMATE

Lumen output varies based on CCT and CRI. An estimate of lumen output of the various CCT/CRI combinations, use correction factors as per table below:

LUMEN ESTIMATE ADJUSTMENT FACTORS				
CCT	2700K	3000K	3500K	4000K
NORMAL(80CRI)	0.91	0.94	0.97	1

## PHOTOMETRIC DATA

AE-SF-F2-4-31-30/35/40-UGR

4 FEET

31 WATTS

ZONAL LUMEN SUMMARY			POLAR LUMINOUS INTENSITY GRAPH
ZONE	LUMENS	% OF FIXTURE	
0-20°	346.93	14.80	
0-30°	717.78	30.60	
0-40°	1139.23	48.60	
0-60°	1895.75	80.90	
0-80°	2280.35	97.40	
0-90°	2313.44	98.80	

AE-SF-F2-8-61-30/35/40-UGR

8 FEET

61 WATTS


ZONAL LUMEN SUMMARY			POLAR LUMINOUS INTENSITY GRAPH
ZONE	LUMENS	% OF FIXTURE	
0-20°	693.86	14.80	
0-30°	1435.56	30.60	
0-40°	2278.49	48.60	
0-60°	3791.49	80.90	
0-80°	4560.70	97.40	
0-90°	4626.88	98.80	

DATE	
PROJECT NAME	
TYPE	
QTY	
ORDERING CODE	AE-SF-F2- - -30/40/CCT- UGR-

## OVERVIEW


### COLOR SELECTABLE

CCT switch to change between 3 CCT – 3000K, 3500K and 4000K – variations from warm to cool light on field.




### MOUNTING

Easy linkable surface mounted fixtures to allow creative designs on the ceiling.




### CONTINUOUS RUNS

Easily connect multiple fixtures together for continuous mounting configuration with the help of our simple link kits .



### LOW UGR LENS

Limit glare and reduce lumen output with our Low UGR lens.



### FINISHES

Standard ERALUX finish in black, white and silver and custom options to provide an elegant look to the fixture's housing.

# F2 UGR

LINEAR SURFACE MOUNT

Linear Architectural Lighting

DATE					
PROJECT NAME					
TYPE					
QTY					
ORDERING CODE	AE-SF-F2-	-	-30/40/CCT-	UGR-	

**Draw your custom shape!**

**1 square = 1ft**

