

GALAXY

eralux[®]

LED COMMERCIAL DOWNLIGHT

Recessed Downlight 4", 6", & 8" Round

The GALAXY is a recessed downlight that offers a range of optical options. Variety of reflectors and trim finishes are available making it an attractive addition. It comes in round shape. It is available in multiple power and wattage options 18/24/30W for 4" & 6" or 30/40/50W for 6" and 8". Multiple CCTs and adjustable beam angles, with low UGR 16, 19 Applications: Art Galleries | Show Rooms | Retail Stores | Hospitality | Office.

DATE	QTY	ACC. QTY	TYPE
PROJECT			
PN			
ACCESSORY PN			
NOTES			

DYNAMIC MENU	
Order Information	Page 2
Dimensions	Page 3
Accessories	Page 5
Photometric Data	Page 6




[Install Instruction link](#)

SPECIFICATIONS

PRODUCT FEATURE

Input Voltage	120-277V
Power Factor	>0.9
Total Harmonic Distortion	<20%
Dimming Page 7	TRIAC & 0-10V (down 10%) for 30W 0-10V (down to 1%) for 50W
CRI	90 CRI
CCT	<div style="display: flex; gap: 10px;"> <div style="border: 1px solid black; border-radius: 50%; width: 20px; height: 20px; background-color: #fff9c4; display: flex; align-items: center; justify-content: center;">27K</div> <div style="border: 1px solid black; border-radius: 50%; width: 20px; height: 20px; background-color: #e0e0e0; display: flex; align-items: center; justify-content: center;">30K</div> <div style="border: 1px solid black; border-radius: 50%; width: 20px; height: 20px; background-color: #e0e0e0; display: flex; align-items: center; justify-content: center;">35K</div> <div style="border: 1px solid black; border-radius: 50%; width: 20px; height: 20px; background-color: #e0e0e0; display: flex; align-items: center; justify-content: center;">40K</div> </div>
Efficacy	~90 lm/W
Size and Power	4 inch 18/24/30W 6 inch 18/24/30W 30/40/50W 8 inch 30/40/50W
Ambient Temperature Range	-25°C to 40°C
Mounting Options	New construction Retrofit
Reflector Finish	
Trim Finish	
Adjustable beam angle	24°-60° for 30W 36°-65° for 50W
Distribution	



PRODUCT CERTIFICATIONS



SYSTEM WARRANTY – 5 YEARS

Eralux will warrant defective drivers, LEDs and boards for 5 years from the date of purchase. This warranty is valid only if the fixture is installed and used as per installation guides and specifications. If a defect is present, Eralux will send drivers and boards at no fee with a thorough replacement. Instructions along with instructions on the return of the defective parts back to Eralux.

LUMEN MAINTENANCE – L70 at 50,000 hours

Rated for 70% initial lumen output at 50,000 hours of operation, operated at 25°C ambient temperature; per guidelines published by the Illuminating Engineering Society (IES).

