

LAGO

eralux®

OUTDOOR LED LIGHT

WALL SCANCES | DIRECT-INDIRECT | CCT/POWER SWITCHABLE

The LAGO outdoor light fixture features an elegant design, offering up and down lighting. With IP65 weatherproof rating, it's suitable for any environment. Its sleek, modern design and robust construction make it perfect for enhancing aesthetic appeal and long-lasting performance in any outdoor setting.

Application: Commercial entrances | Outdoor landscapes | Facades | Residential Exteriors



DATE	QTY	ACC. QTY	TYPE
PROJECT			
PN			
ACCESSORY PN			
NOTES			

DYNAMIC MENU	
Order Information	Page 1
Dimensions	Page 2
Accessories	Page 4
Photometric Data	Page 4

[Install Instruction link](#)



SPECIFICATIONS

Input Voltage	120-347V
Power Factor	>0.9
Total Harmonic Distortion	<20%
Dimming	0-10V dimming
CRI	80 CRI
CCT	<div style="display: flex; gap: 10px;"> <div style="border: 1px solid black; border-radius: 50%; width: 20px; height: 20px; background-color: #fff9c4; display: flex; align-items: center; justify-content: center;">27K</div> <div style="border: 1px solid black; border-radius: 50%; width: 20px; height: 20px; background-color: #fff176; display: flex; align-items: center; justify-content: center;">30K</div> <div style="border: 1px solid black; border-radius: 50%; width: 20px; height: 20px; background-color: #bbdefb; display: flex; align-items: center; justify-content: center;">40K</div> <div style="border: 1px solid black; border-radius: 50%; width: 20px; height: 20px; background-color: #cfe2f3; display: flex; align-items: center; justify-content: center;">50K</div> </div>
Efficacy	~90 lm/W
Power	20/16/12/8W
Ambient Temperature Range	-40°C to 50°C
Mounting Options	Wall Mount
Fixture Finish	Black 
Controls	Integrated Photocell
Lens	Polycarbonate Lens
Housing	Round Square
Protection	IP65; Water and Dust resistance 4kV Surge Protector
Distribution	Adjustable From 0° to 100° direct/indirect 

PRODUCT FEATURES



PRODUCT CERTIFICATIONS



SYSTEM WARRANTY – 5 YEARS

Eralux will warrant defective drivers, LEDs and boards for 5 years from the date of purchase. This warranty is valid only if the fixture is installed and used as per installation guides and specifications. If a defect is present, Eralux will send drivers and boards at no fee with a thorough replacement instructions along with instructions on the return of the defective parts back to Eralux.

LUMEN MAINTENANCE – L80 at 50,000 hours

Rated for 80% initial lumen output at 50,000 hours of operation, operated at 25°C ambient temperature per guidelines published by the Illuminating Engineering Society (IES).