

OVA

LED COMMERCIAL DOWNLIGHT

Surface Mount Disk | 4" & 6" Round

The OVA Series is round semi oval shape surface mounted downlight disk. Its selectable CCT switch lets you adjust the color temperature from 2700K to 5000K. Available in 4" & 6" aperture sizes with 10W & 15W respectively to give an output of 82Lm/W, providing a versatile lighting option for any space, in addition to the surface mount it can be retrofit installed into can with the appropriate accessories.

Applications: Office | Retail stores | Hotels | Restaurants | Home interior | Library Etc.

	DATE	QTY	ACC. QTY	TYPE
PROJECT				
PN				
ACCESSORY PN				
NOTES				



DYNAMIC MENU

Order Information	Page 2
Dimensions	Page 3
Accessories	Page 4
Photometric Data	Page 6

[Install Instruction link](#)

SPECIFICATIONS

Input Voltage	120V	
Power Factor	>0.9	
Total Harmonic Distortion	<20%	
Dimming Page 6	TRIAC	
CRI	90 CRI	
CCT	27K 30K 35K 40K 50K	
Efficacy	~ 82 LPW	
Size	4"	6"
Power	10W	15W
Ambient Temperature Range	-20°C to 40°C	
Mounting	Surface mount Retrofit into can	
Finish	White	

Distribution



PRODUCT FEATURES



PRODUCT CERTIFICATIONS



SYSTEM WARRANTY – 5 YEARS

Eralux will warrant defective drivers, LEDs and boards for 5 years from the date of purchase. This warranty is valid only if the fixture is installed and used as per installation guides and specifications. If a defect is present, Eralux will send drivers and boards at no fee with a thorough replacement instructions along with instructions on the return of the defective parts back to Eralux.

LUMEN MAINTENANCE – L70 at 50,000 hours

Rated for 70% initial lumen output at 50,000 hours of operation, operated at 25°C ambient temperature; per guidelines published by the Illuminating Engineering Society (IES).